



Image may differ from product. See technical specification for details.

LAGG 18M

Grease pump for use on drums

SKF manual grease pump LAGG 18M is designed to supply grease at high pressure from a 18 kg drum. This is useful when large housings have to be filled or when numerous points have to be lubricated. It is also possible to top up centralised lubrication system reservoirs.

- High pressure
- Reliable and tested for SKF greases in 18 kg drums
- Easy and ready to use
- Long tubing included
- Manual operation

Overview

Dimensions

Suitable drum inner diameter	265 – 285 mm
Suitable drum inside height (max)	420 mm

Performance

Maximum pressure	50 MPa
Maximum pressure	500 bar

Properties

Recommended applications	grease pump for drums or pails designed for high pressure applications can be connected directly on greasing points suitable for filling centralised lubricating grease systems
For type/size of grease drum	18 kg grease pail
Operation	air operated grease pump
Mobility	stationary
NLGI class of lubricant (max)	2
Connection	greasing point: DIN 71412
Air pressure	-
Volume per stroke	1.6 ml
Hose	Yes, 3.5 Meter
Optional Trolley	LAGT 18 - 50
Power source	manual
Material	steel, rubber hose
Material handle	steel with plastic grip
Ambient temperature range	5 – 50 °C
Recommended storage temperature	10 – 40 °C
Relative humidity	< 65 %
Content	grease pump with pump handle, drum cover plate, drum followerplate, high pressure hose

Logistics

Product net weight	5.81 kg
eClass code	23-06-91-06
UNSPSC code	15121902

Compatible products

Spare part

Spare pistol for Air-driven grease pumps	LAGG-P1
--	-------------------------

Accessory

Grease coupler	LAGC S
----------------	------------------------

Grease trolley for grease drums/ pails, for Air-driven grease pumps	LAGT 18-50
---	----------------------------

Grease trolley for grease drums/ pails, for Air-driven grease pumps	LAGT 18-50F
---	-----------------------------

Recommended product

Grease meter, measuring grease discharge	LAGM 1000E
--	----------------------------

Extreme pressure bearing grease	LGEP 1/18
---------------------------------	---------------------------

High load, extreme pressure bearing grease	LGEP 2/18
--	---------------------------

Extremely high viscosity bearing grease with solid lubricants	LGEV 2/18
---	---------------------------

General purpose food grade grease	LGFG 2/18
-----------------------------------	---------------------------

High load, water resistant and wide temperature food grade grease	LGFQ 2/18
---	---------------------------

EAL Biodegradable bearing grease	LGGB 2/18
----------------------------------	---------------------------

High load, high temperature, high viscosity bearing grease	LGHB 2/18
--	---------------------------

High load, water resistant, high temperature bearing grease	LGHC 2/18
---	---------------------------

High performance, high temperature bearing grease	LGHP 2/18
---	---------------------------

Electric motor bearing grease	LGHQ 2/18
-------------------------------	---------------------------

Wide temperature lubrication systems grease	LGLS 0/18
---	---------------------------

High viscosity lubrication systems grease	LGLS 2/18
---	---------------------------

Low temperature, extremely high speed bearing grease	LGLT 2/18
--	---------------------------

General purpose industrial and automotive bearing grease	LGMT 2/18
--	---------------------------

General purpose industrial and automotive bearing grease	LGMT 3/18
General purpose, high load industrial bearing grease	LGNL 2/18
General purpose, high load bearing grease	LGNL 3/18
Biodegradable grease for total loss applications	LGTE 2/18
Wide temperature range, extreme pressure, high load bearing grease	LGWA 2/18
Extreme pressure low temperature bearing grease	LGWM 1/18
High loads, wide temperature bearing grease	LGWM 2/18

Terms of use